

VeriFone Vx510

Dimensions:

- Terminal weight: 480g
- Terminal size:
209mm (L) x 102mm (W) x 72mm (H)
- Pinpad weight: 340g
- Pinpad size:
155mm (L) x 95mm (W) x 51mm (H)
- Curly cord length:
1.2m at comfortable stretch

Features at a glance:

- 3DES compliant / EMV capable
- Standard EFTPOS plus value add services
- Two piece unit (terminal and separate pinpad)
- Multi-merchant
- Easy to use menu system with staff training mode
- Fast quiet thermal printer with easy to load drop in paper rolls
- 'ATM' style interface with large backlit display

Accessories available to purchase:

- Terminal and pinpad splash protectors
- Stationery - paper rolls and cleaning cards
- Pinpad extension cord - up to 3m stretched

VeriFone Vx570

Dimensions:

- Weight: 750g (includes swivel stand)
- Size of terminal :
209mm (L) x 102mm (W) x 78mm (H)

Features at a glance:

- 3DES compliant / EMV capable
- Standard EFTPOS (debit and credit card transactions only)
- Multi-merchant capable
- Pre-authorisation and completion
- Easy to use menu system with staff training mode
- Fast quiet thermal printer with easy to load drop in rolls virtually eliminating paper jams
- Highly readable anti-glare white backlit display and bold menu prompts
- Extremely fast 32-bit processor

Accessories available to purchase:

- Terminal splash protector
- Stationery - paper rolls, cleaning cards

VeriFone Vx610

Dimensions:

- Terminal weight: 660g
- Terminal size:
209mm (L) x 102mm (W) x 70mm (H)

Features at a glance:

- 3DES compliant / EMV capable
- Standard EFTPOS (debit and credit card transactions)
- Multi-merchant
- Pre-authorisation and completion
- Light weight leather carry case to protect terminal
- Easy to use menu system with staff training mode
- Fast quiet thermal printer with easy to load drop in paper rolls
- 'ATM' style interface with large backlit display and bold menu prompts
- Rechargeable battery

Accessories available to purchase:

- Terminal splash protectors
- Spare battery
- Car charger
- Stationery - paper rolls and cleaning cards

Ingenico 5100

Dimensions & Weight

- 21 x 9.5 x 7.5 cm (8.27 x 3.74 x 2.95 in.)
1.32 lb. (600 g)

Specifications:

- Processor 32 bit ARM processor
Memory 1 MB SRAM and 4 MB Flash
Upgradeable to 2 MB SRAM and 8 MB of Flash
Printer 15 lines per second thermal printer
Display LCD display, 128x64 pixels and graphics capability
Keypad 18 backlit keys including 3 screen addressable
- Communication V3.4 modem, transfers up to 33.6K bits per second (bps)
TCP/IP for use as a thin client
TCP/IP – POP3, SMTP, SSL
Magnetic stripe reader Tracks 1, 2 & 3
Smart card reader EMVco approved Level 1
UNICAPT 32 EMV Level 2 approved

EFT930-G

Technical characteristics

- Dimensions and weight:
79x180x57mm/circa 475g.
- RISC 32 Bits ARM9 (200 Mips)
microprocessor

Security:

- 32 bits security coprocessor (DES, 3 DES, MK/SK, DUKPT, RSA,...)
- Visa PED certified (on and off-line mode)

Memory: FLASH 8 MB; SDRAM 8 MB

- Variable frequency EMV smart card reader
- Three SAM (Security Access Module) readers +1 SIM
- Magnetic reader: tracks 1, 2
- Graphic backlit display: 128 x 64 pixels
- Backlit keypad: 16 keys, 3 of which are colour
- Functional backlit pad: 6 keys
- Thermal printing: 15 L/S—“Easy loading”
- Ticket: 58 mm - Roll: III 40 mm
- Buzzer
- Communication: GPRS/GSM (900, 1800, 1900)

- Batteries NiMh: 180 trans. typical / standby 200h
 - (GPRS)
 - Terminal connections: USB slave + USB master
 - Terminal options
 - Magnetic reader: tracks 1, 2, 3
 - Second smart card reader
 - MMC or SDCard connector.
 - DS930 PM base
 - V22 modem, V22bis, V32bis incoming and outgoing calls
 - Simplified RS-232C serial link
 - Battery charger: 110-230 volts. DS930 C
 - Battery charger: 110-230 volts. TC930 travel charger
 - 110-230 volts.
 - Software
- Development station and associated modules:
- SDK Telium®
 - Terminal Management System: TMS Telium®.